

§ 98.445

40 CFR Ch. I (7–1–13 Edition)

American Society of Mechanical Engineers (ASME), the American Petroleum Institute (API), and the North American Energy Standards Board (NAESB).

(4) You must ensure that any flow meter calibrations performed are National Institute of Standards and Technology (NIST) traceable.

(f) *General.*

(1) If you measure the concentration of any CO₂ quantity for reporting, you must measure according to one of the following. You may use an appropriate standard method published by a consensus-based standards organization if such a method exists or an industry standard practice.

(2) You must convert all measured volumes of CO₂ to the following standard industry temperature and pressure conditions for use in Equations RR-2, RR-5 and RR-8 of this subpart: Standard cubic meters at a temperature of 60 degrees Fahrenheit and at an absolute pressure of 1 atmosphere.

(3) For 2011, you may follow the provisions of § 98.3(d)(1) through (2) for best available monitoring methods only for parameters required by paragraphs (a) and (b) of § 98.443 rather than follow the monitoring requirements of paragraph (a) of this section. For purposes of this subpart, any reference to the year 2010 in § 98.3(d)(1) through (2) shall mean 2011.

[75 FR 75078, Dec. 1, 2010, as amended at 76 FR 73906, Nov. 29, 2011]

§ 98.445 Procedures for estimating missing data.

A complete record of all measured parameters used in the GHG quantities calculations is required. Whenever the monitoring procedures cannot be followed, you must use the following missing data procedures:

(a) A quarterly flow rate of CO₂ received that is missing must be estimated as follows:

(1) Another calculation methodology listed in § 98.444(a)(1) must be used if possible.

(2) If another method listed in § 98.444(a)(1) cannot be used, a quarterly flow rate value that is missing must be estimated using a representative flow rate value from the nearest previous time period.

(b) A quarterly mass or volume of contents in containers received that is missing must be estimated as follows:

(1) Another calculation methodology listed in § 98.444(a)(2) must be used if possible.

(2) If another method listed in § 98.444(a)(2) cannot be used, a quarterly mass or volume value that is missing must be estimated using a representative mass or volume value from the nearest previous time period.

(c) A quarterly CO₂ concentration of a CO₂ stream received that is missing must be estimated as follows:

(1) Another calculation methodology listed in § 98.444(a)(3) must be used if possible.

(2) If another method listed in § 98.444(a)(3) cannot be used, a quarterly concentration value that is missing must be estimated using a representative concentration value from the nearest previous time period.

(d) A quarterly quantity of CO₂ injected that is missing must be estimated using a representative quantity of CO₂ injected from the nearest previous period of time at a similar injection pressure.

(e) For any values associated with CO₂ emissions from equipment leaks and vented emissions of CO₂ from surface equipment at the facility that are reported in this subpart, missing data estimation procedures should be followed in accordance with those specified in subpart W of this part.

(f) The quarterly quantity of CO₂ produced from subsurface geologic formations that is missing must be estimated using a representative quantity of CO₂ produced from the nearest previous period of time.

(g) You must estimate the mass of CO₂ emitted by surface leakage that is missing as required by your approved MRV plan.

(h) You must estimate other missing data as required by your approved MRV plan.

[75 FR 75078, Dec. 1, 2010, as amended at 76 FR 73906, Nov. 29, 2011]

§ 98.446 Data reporting requirements.

In addition to the information required by § 98.3(c), report the information listed in this section.